

Wavetronix Module

ATMS.now provides a direct “point and click” interface with Wavetronix model “Smart Senor 105” radar counting units that are equipped with the SNMP interface option. By adding this module to ATMS.now, your GIS map interface will be equipped with real-time information about Volume, Occupancy, and Speed for each sensor in the field.

External Detector Report

2/3/2012

ID : 2866

Name : 4031VDS1

Begin Date : 02/03/2012

Begin Time : 14:00.00

End Date : 02/03/2012

End Time : 14:30.00

Date/Time	Lane 1			Lane 2			Lane 3			Lane 4			Lane 5			Lane 6			Lane 7			Lane 8			Lane 9			Lane 10					
	Vol	Occ	Spd	Vol	Occ	Spd	Vol	Occ	Spd	Vol	Occ	Spd	Vol	Occ	Spd	Vol	Occ	Spd	Vol	Occ	Spd	Vol	Occ	Spd	Vol	Occ	Spd						
2/3/2012 2:00:00PM	40	6	33	44	7	33	46	9	32	44	8	31	8	1	28	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
2/3/2012 2:15:00PM	44	6	36	47	7	35	42	9	29	40	16	27	5	1	29	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total Volume	84			91			88			84			13			0			0			0			0			0			0		
Average Volume	42.00			45.50			44.00			42.00			6.50			0.00			0.00			0.00			0.00			0.00			0.00		

The sample External Detector Report pictured above displays the data that can be reported from the Wavetronix device.

